

PFA lined reducer tri-clamp fitting

TYPE PLRTC

Fitting standard: 3A.

FEP or PTFE liners are available.

Virgin and anti-static liners are available.

Remark: Can be customized.



Part no.	Fitting material	Size	A(mm)	B(mm)	L(mm)
PLRTC040025S4	SS304+PFA	1.5"-1.0"	50.5	50.5	76.2
PLRTC050025S4	SS304+PFA	2.0"-1.0"	64	50.5	12.7
PLRTC050040S4	SS304+PFA	2.0"-1.5"	64	50.5	96.2
PLRTC065025S4	SS304+PFA	2.5"-1.0"	77.5	50.5	177.8
PLRTC065040S4	SS304+PFA	2.5"-1.5"	77.5	50.5	127
PLRTC065050S4	SS304+PFA	2.5"-2.0"	77.5	64	76.2
PLRTC080025S4	SS304+PFA	3.0"-1.0"	91	50.5	282.5
PLRTC080040S4	SS304+PFA	3.0"-1.5"	91	50.5	177.8
PLRTC080050S4	SS304+PFA	3.0"-2.0"	91	64	127
PLRTC080065S4	SS304+PFA	3.0"-2.5"	91	77.5	76.2
PLRTC100040S4	SS304+PFA	4.0"-1.5"	119	50.5	282.5
PLRTC100050S4	SS304+PFA	4.0"-2.0"	119	64	231.5
PLRTC100050S4	SS304+PFA	4.0"-2.5"	119	77.5	180.9
PLRTC100080S4	SS304+PFA	4.0"-3.0"	119	91	130.1