

Food Grade Rubber Hose







Applications:

For hot water washing in food processing plants. Also for transfer of hot liquid foodstuffs such as safe fat food, milk, fruit juice, drinks, wine, oil, potable water and alcohol up to 96%. . ID 9.5 to 25.4mm, suitable for reel mounted applications.

Construction:

Tube: White NBR, oil resistant, smooth.

Reinforcement: Synthetic textile.

Cover: Blue CSM, oil and weather resistant, smooth for ID 9.5 to 25.4 mm, fabric impression for ID 32 to 76mm.

Temperature range: -30° C \sim +120 $^{\circ}$ C

Standard / Approval: FDA 21 CFR 177.2600.

Part no.	ID		OD	Bending radius	Working pressure	Bursting pressure	Length
	inch	mm	mm	mm	bar	bar	m
FSC010	3/8"	9.5	17	55	20	60	100
FSC013	1/2"	12.7	22	65	20	60	100
FSC016	5/8"	15.9	25	85	20	60	60
FSC019	3/4"	19	30	100	20	60	60
FSC025	1"	25.4	37	125	20	60	60
FSC032	1-1/4"	32	44	250	10	40	40
FSC038	1-1/2"	38	51	300	10	40	40
FSC051	2"	50.8	66	400	10	40	40
FSC064	2-1/2"	63.5	80	500	10	40	40
FSC076	3"	76	94	600	10	40	40