

High Flow Water Spray Gun

Description:

The HF Water Spray Gun was specifically designed to prevent accidental spray. Its unique cover design is not only durable but also prevents the front mounted levers which reduce hand fatigue and offer smooth lever action, from being accidentally activated when the nozzle is dropped. It also comes with a trigger locking mechanism for a safe and secure method of maintaining the nozzle open at any spray pattern.

Variable spray patterns, adjustable from fan spray to solid stream, is one of the many features offered by the HF water gun. Water conservation is assured upon release of the lever by the drip-free automatic shut off feature.

Rating: 150PSI/93°C.

Maximum tested operating pressure of 500 PSI. Not for use with steam.

Applications: Effectively clean floor, equipment of workplace in a food factory, pharmacy factory, biology laboratory, petrochemical industry and so on.

Color: Can be customized.

Part no.	Thread	Colour	Material	Weight	Inlet Pressure	Flow Rate
	inch	-	-	kg	(PSIG)	(GPM)
HF	1/2"NPT	CJan	SS	0.6	25	4.39
	1/2"NPT	CJan	SS	0.6	50	6.54
	1/2"NPT	CJan	SS	0.6	75	8.18
	1/2"NPT	CJan	SS	0.6	100	9.56
	1/2"NPT	CJan	SS	0.6	125	10.83
	1/2"NPT	CJan	SS	0.6	150	11.89