

PFA Lined Reducer Tri-clamp Fitting and Flange

TYPE PLRLTC

Tri-clamp standard: 3A.

Flange standard: EN PN16.

Other flange standards are available.

FEP liners are available.

Virgin and anti-static liners are available.

Remark: Can be customized.



Part no.	Fitting material	Size	A(mm)	B(mm)	L(mm)
PLRLTC040025S4	SS304+PFA	1.5"-1.0"	50.5	85	92.2
PLRLTC050025S4	SS304+PFA	2.0"-1.0"	64	85	143
PLRLTC050040S4	SS304+PFA	2.0"-1.5"	64	110	94.2
PLRLTC065025S4	SS304+PFA	2.5"-1.0"	77.5	85	195.8
PLRLTC065040S4	SS304+PFA	2.5"-1.5"	77.5	110	147
PLRLTC065050S4	SS304+PFA	2.5"-2.0"	77.5	125	98.2
PLRLTC080025S4	SS304+PFA	3.0"-1.0"	91	85	298.5
PLRLTC080040S4	SS304+PFA	3.0"-1.5"	91	110	195.8
PLRLTC080050S4	SS304+PFA	3.0"-2.0"	91	125	149
PLRLTC080065S4	SS304+PFA	3.0"-2.5"	91	145	100.2
PLRLTC100040S4	SS304+PFA	4.0"-1.5"	119	110	300.5
PLRLTC100050S4	SS304+PFA	4.0"-2.0"	119	125	253.7
PLRLTC100050S4	SS304+PFA	4.0"-2.5"	119	145	204.9
PLRLTC100080S4	SS304+PFA	4.0"-3.0"	119	160	156.1

