

## PFA lined coupler with fixed flange

### TYPE PLDL



**Camlock standard:** A-A-59326/DIN 2828

FEP or PTFE liners are available.

Virgin and anti-static liners are available.

**Remark:** Can be customized.

| Part no.  | Fitting material | Size   | Flange standard | D±0.1<br>mm | D2 min<br>mm |
|-----------|------------------|--------|-----------------|-------------|--------------|
| PLDL019S4 | SS304+PFA        | 3/4"   | EN PN16         | 32.4        | 90.0         |
| PLDL025S4 | SS304+PFA        | 1"     | EN PN16         | 37.3        | 96.0         |
| PLDL032S4 | SS304+PFA        | 1-1/4" | EN PN16         | 46.0        | 111.0        |
| PLDL038S4 | SS304+PFA        | 1-1/2" | EN PN16         | 54.0        | 115.0        |
| PLDL050S4 | SS304+PFA        | 2"     | EN PN16         | 63.8        | 122.0        |
| PLDL063S4 | SS304+PFA        | 2-1/2" | EN PN16         | 76.5        | 125.0        |
| PLDL076S4 | SS304+PFA        | 3"     | EN PN16         | 92.2        | 132.0        |
| PLDL102S4 | SS304+PFA        | 4"     | EN PN16         | 120.3       | 137.0        |